



## 2.2 Jumper Settings

### 2.2.1 Common jumpers

Common jumpers are those jumpers which should be set the same on the different evaluation boards, no matter which parts and packages. The **Table 2** shows the common jumpers setting on the evaluation board:

**TABLE 2: COMMON JUMPERS SETTINGS**

JUMPERS	FUNCTIONS	COMMENTS
J10	I/O Interface with mother board	Installed. Necessary to connect UART signals mother board.
J11	I/O Interface with mother board	Installed. Necessary to connect UART signals with mother board.
J9	I/O Interface with mother board	Option. Not necessary for single channel UART..
J12	I/O Interface with mother board	Option. Not necessary for single channel UART.

### 2.2.2 32-QFN package jumper

The following **Table 3** jumper settings apply to the 32-QFN package:

**TABLE 3: JUMPER SETTINGS FOR 32-QFN PACKAGE**

JUMPERS	FUNCTIONS	COMMENTS
J6	Power supply to UART	Trace between 1 & 2
J8	Selects POWERSAVE mode	Jumper in 1&2 enables POWERSAVE mode Jumper out 1&2 disables POWERSAVE mode
JP1	Selects crystal or external clock	Jumper in 1&2 and 4& 5 selects crystal <ul style="list-style-type: none"> <li>■ Trace between 1 &amp; 2</li> <li>■ Trace between 4 &amp; 5</li> </ul> Jumper out and pin 3 selects external clock

### 2.2.3 25-BGA package

The following **Table 4** jumper setting applies to the 25-BGA package:

**TABLE 4: JUMPER SETTINGS FOR 25-BGA PACKAGE**

JUMPERS	FUNCTIONS	COMMENTS
J4	Power supply to UART	Trace between 1 & 2
JP2	Selects crystal or external clock	Jumper in 1&2 and 4& 5 selects crystal <ul style="list-style-type: none"> <li>■ Trace between 1 &amp; 2</li> <li>■ Trace between 4 &amp; 5</li> </ul> Jumper out and pin 3 selects external clock
J8	Selects POWERSAVE mode	Jumper in 1&2 enables POWERSAVE mode Jumper out 1&2 disables POWERSAVE mode
J5	Selects external loopback on UART side	Jumper in 1&2 selects external loopback on UART side Jumper out 1&2 deselects external loopback on UART side



### 2.2.4 24-QFN package

The following **Table 5** jumper setting applies to the 24-QFN package:

**TABLE 5: JUMPER SETTINGS FOR 24-QFN PACKAGE**

JUMPERS	FUNCTIONS	COMMENTS
J1	Power supply to UART	Trace between 1 & 2
J3	Selects different type of clocks	Jumper in 1&2 selects crystal Jumper in 2&3 selects external clock ■ Trace between 2 & 3
JP3	Selects crystal or external clock	Jumper in 1&2 and 4& 5 selects crystal ■ Trace between 1 & 2 ■ Trace between 4 & 5 Jumper out and pin 3 selects external clock
J8	Selects POWERSAVE mode	Jumper in 1&2 enables POWERSAVE mode Jumper out 1&2 disables POWERSAVE mode

### 3.0 DRIVERS

It is recommended that you contact [uarttechsupport@exar.com](mailto:uarttechsupport@exar.com) to inquiry and request drivers.

### 4.0 SAMPLE INITIALIZATION ROUTINE AND SUPPORT

For a sample initialization routine or if there are any questions, send an e-mail to [uarttechsupport@exar.com](mailto:uarttechsupport@exar.com).

### NOTICE

EXAR Corporation reserves the right to make changes to the products contained in this publication in order to improve design, performance or reliability. EXAR Corporation assumes no responsibility for the use of any circuits described herein, conveys no license under any patent or other right, and makes no representation that the circuits are free of patent infringement. Charts and schedules contained here in are only for illustration purposes and may vary depending upon a user's specific application. While the information in this publication has been carefully checked; no responsibility, however, is assumed for inaccuracies.

EXAR Corporation does not recommend the use of any of its products in life support applications where the failure or malfunction of the product can reasonably be expected to cause failure of the life support system or to significantly affect its safety or effectiveness. Products are not authorized for use in such applications unless EXAR Corporation receives, in writing, assurances to its satisfaction that: (a) the risk of injury or damage has been minimized; (b) the user assumes all such risks; (c) potential liability of EXAR Corporation is adequately protected under the circumstances.

Copyright 2009 EXAR Corporation

Datasheet February 2009.

Send your UART technical inquiry with technical details to hotline: [uarttechsupport@exar.com](mailto:uarttechsupport@exar.com).

Reproduction, in part or whole, without the prior written consent of EXAR Corporation is prohibited.